



## LYNGSOE STAFF WORKSTATION™

### UNIVERSAL RFID TAG READING AND WRITING FOR YOUR LIBRARY MANAGEMENT SYSTEM

#### INTEGRATES WITH YOUR LMS/ILS

If your library system is providing a full integration solution, the Lyngsoe Staff Mate™ software can be fully embedded into your library system. Your library system will automatically harness the software when reading materials' ID or checking materials in or out. The Staff Mate application also enables you to handle theft protection by simply activating or deactivating the AFI/EAS in the RFID tags.

#### KEYBOARD SHORTCUTS

Even if your library system does not provide full integration, you can activate the Staff Mate software through keyboard shortcuts to handle processes such as material ID transferring or theft protection. You can easily configure keyboard shortcuts to fit your processes.

#### EASY CONVERSION FROM BARCODE TO RFID

In the library conversion mode, a few simple steps quickly guide you through the reading of barcodes from a barcode scanner and writing these on the RFID tags. The RFID software is designed in compliance with the ISO 28560 standard.

#### PROTECTED CONFIGURATION

To prevent unwanted settings, the configuration is protected by a password for administrators. You can select settings in the drop-down menus to fit your library's specific needs.

#### FLEXIBLE INSTALLATION

There are two different installation options to choose from, based on the preferences of the library. The tabletop model has a stylish design and enables reading multiple items at the same time (stack reading). The other option is to place it under the staff station table, where it will be out of sight and does not take up any space on the table surface.

#### BENEFITS

- Easy conversion from barcode to RFID
- Password protected configuration
- Easy to install with the installation wizard
- Shielded HF pad antenna with integrated reader



## SPECIFICATIONS

## LYNGSOE STAFF WORKSTATION™

### GENERAL

RFID data models ISO28560, DDM, KATVE, TechLogic, TV2, 3M, TRC, ITG, ITG2, Finnish Nec, ISO28560-2, Dutch, French, Intellident/UK1, DM12

### COMPATIBILITY AND PROGRAMS

Library systems Alma, Aurora, BiblioFil, Book-it, Cicero, Integra, Library, Micromarc, Quria, Sierra, Voyager, Axiell, Koha

### STAFF MATE SOFTWARE

Data models ISO28560-3 (Read and programming)  
Operating system Windows 7 or newer (on required library PC)  
RFID reader drivers To Windows 7 or newer  
Hardware interface USB  
Windows detectors VTLS, Voyager, Soprano, Polaris, Libra, Horizon

### FEIG SPAD102 SHIELDED HF PAD ANTENNA WITH INTEGRATED READER

Dimensions (L x W x H) 376 mm x 276 mm x 27 mm / 14.8" x 10" x 1.1"  
Weight 2 kg / 4.4 lbs  
Colors Black, acrylic glass and white (similar to RAL 9003)  
Reader connectivity Integrated in pad antenna  
Supply voltage 12-24V DC  
Indicator Optical, 1 LED  
Supportal transponders ISO 15693, ISO 18000-3 Mode 1  
Operation frequency 13.56 Mhz  
Standard conformity EN 301 489, EN 62368-1, EN 50364, EN 300 330, FCC 47 CFR, IC RSS-GEN, RSS-210



[www.lyngsoesystems.com](http://www.lyngsoesystems.com)  
[library@lyngsoesystems.com](mailto:library@lyngsoesystems.com)

