



ES001

It passed ISO9001:2008 international quality system certification from 2002 up to now.

Product Specification

- Solid wood and cristal glass combination design, flow linear shape, good transparent effect. And meets the requirement of the Standard of the Disabled Barrier Free Access.
- Applicant for books, pharmacy, cosmetics etc. Blending with surroundings, easy operation, low cost. with ability of anti electronic interference and resistance to aluminium foil block and tinfoil block.

Unit Dimension	148*54*4cm(H*W*D)
Working Voltage	110V-240V
Working Environment	-10°C-40°C
Material	Advanced-Resin-Glass+MDF
Detection	Height:170cm Width:80cm
Packing Details	1set/ctn,34.0kgs/ctn,151*62*18cm
Controller-Box Packing Details	1set/ctn,6.5kgs/ctn, 43*33*32cm



ES002

It passed ISO9001:2008 international quality system certification from 2002 up to now.

Product Specification

- Solid wood and cristal glass combination design, flow linear shape, good transparent effect. And meets the requirement of the Standard of the Disabled Barrier Free Access.
- Applicant for books, pharmacy, cosmetics etc. Blending with surroundings, easy operation, low cost. with ability of anti electronic interference and resistance to aluminium foil block and tinfoil block.

Unit Dimension	145*62*4cm(H*W*D)
Working Voltage	110V-240V
Working Environment	-10°C-40°C
Material	Advanced-Resin-Glass+MDF
Detection	Height:170cm Width:80-100cm
Packing Details	1set/ctn,36.0kgs/ctn,150*70*30cm
Controller-Box Packing Details	1set/ctn,6.5kgs/ctn, 43*33*32cm



ES003

It passed ISO9001:2008 international quality system certification from 2002 up to now.

Product Specification

- Adapting FRP material, anti-aging corrosion resistance, durable. And has a precise alarm and high detection rate.
- Can work with people counting, compatible with labels, green energy.
- with ability of anti electronic interference and resistance to aluminium foil block and tinfoil block.

Unit Dimension	152*44*3cm(H*W*D)
Working Voltage	110V-240V
Working Environment	-10°C-40°C
Material	Advanced-Resin-Glass
Detection	Height:170cm Width:80cm
Packing Details	1set/ctn,24.0kgs/ctn,158*50*18cm
Controller-Box Packing Details	1set/ctn,6.5kgs/ctn, 43*33*32cm



ES008

It passed ISO9001:2008 international quality system certification from 2002 up to now.

Product Specification

- Pure acrylic carefully carved, crystal transparent, streamlined, and transparent effect.
- It has a precise alarm and high detection rate.
- Can work with people counting, compatible with labels, green energy
- with ability of anti electronic interference and resistance to aluminium foil block and tinfoil block.

Unit Dimension	150*40*3cm(H*W*D)
Working Voltage	110V-240V
Working Environment	-10°C-40°C
Material	Acrylic
Detection	Height:170cm Width:80-100cm
Packing Details	1set/ctn,37.0kgs/ctn,164*67*13cm
Controller-Box Packing Details	1set/ctn,6.5kgs/ctn, 43*33*32cm



EL002 EM BOOK LABEL

Size:12cm or 16cm  
 Material:Cobalt-Based  
 Characteristic:Double Side Adhesive  
 Deactivable/Non-Deactivable  
 Length 16cm Packing Details:  
 50000pcs/ctn,20.0kgs/ctn,  
 41\*33\*26cm



EL002 EM BOOK LABEL



EL004 EM BOOK LABEL

Size:12cm or 16cm  
 Material:Cobalt-Based  
 Characteristic:Double Side Adhesive  
 Deactivable/Non-Deactivable  
 Length 12cm Packing Details:  
 20000pcs/ctn,10.0kgs/ctn,48\*38\*17cm  
 Length 16cm Packing Details:  
 20000pcs/ctn,11.0kgs/ctn,48\*38\*17cm



EL004 EM BOOK LABEL



EL005 EM LABEL

Size:1\*4/1\*5/1\*6cm or Customized  
 Material:Cobalt-Based  
 Characteristic:Single Side Adhesive  
 Deactivable/Non-Deactivable  
 Packing Details:20000pcs/ctn,5.8kgs/ctn,  
 27\*22\*29cm



EL005 EM LABEL



EL008 EM CD LABEL

Size:11.4cm Dia'  
 Strip Size:10cm  
 Material:Cobalt-Based  
 Characteristic:Single Side Adhesive  
 Deactivable/Non-Deactivable  
 Packing Details:4000pcs/ctn,9.0kgs/ctn,  
 48\*25\*14cm



EL008 EM CD LABEL



**ED002  
ACTIVATOR/DEACTIVATOR**

Unit Dimension:27\*23\*10cm  
 Working Voltage:110V-240V  
 Deactivation Height:≤10cm  
 Packing Details:1pc/ctn,8.0kgs/ctn,35\*29\*18cm



**ED004  
ACTIVATOR/DEACTIVATOR/DETECTOR**

Unit Dimension:34\*22\*9cm  
 Working Voltage:110V-240V  
 Detection Height:≤2cm  
 Deactivation Height:≤5cm  
 Packing Details:1pc/ctn,10.0kgs/ctn,41\*33\*18cm

